

INDIANA LIMESTONE - STANDARD GRAY™

● LIMESTONE



HONED

DESCRIPTION

This neutral limestone possesses a subdued palette featuring light to medium shades of gray. A restrained, underlying vein pattern and subtle grain movement are visible in the fine to medium grained surface.

QUARRY OPERATING SINCE | ANNUAL PRODUCTION

1897

12 000 m³ and more
(423 776 cu. ft.)

AVAILABLE FINISHES


Honed Bush-Hammered Split Face
Sandblasted Wire Brushed Tumbled

APPLICATIONS

Exterior Vertical
Interior Commercial
Horizontal Residential

PHYSICAL TEST RESULTS

		Imperial	Metric
Absorption by weight	ASTM C97	7.5%	7.5%
Density	ASTM C97	144 lb/ft ³	2 306.66 kg/m ³
Compressive strength	ASTM C170	4 000 Psi	27.58 MPa
Modulus of rupture	ASTM C99	700 Psi	4.83 MPa



QUARRY LOCATION:
Bloomington, IN, U.S.A.

NATURALLY SUSTAINABLE™

Health Product Declaration® available 2020
ANSI/NSC 373 Certified Quarry since 2018



POLYCOR

QUARRY OWNERS | BLOCKS | SLABS | TILES | LANDSCAPING PRODUCTS | CURBS

polycor.com

Computer generated images and printed reproductions may not accurately match natural stone colors.